



www.hylineoffroad.com

1507 C West Park Avenue ~ Perkasio, PA 18944

Tel: 1.888.495.4631 ~ Fax: 215.257.4364

**Proudly Made In USA**

**Installation Instructions:**

JK Tube Step Rocker Panel

Part Number: **400.300.110**

**Vehicle Fitment:**

2007-Present Jeep Wrangler


2-Door Only

### Parts List

**Qty:**

- 1 Driver Rock Slider – RED Dot
- 1 Passenger Rock Slider – GREEN Dot
- 1 Driver Drill Template – RED Dot
- 1 Passenger Drill Template – GREEN Dot
- 8 3/8-16 Gr 5 Hex Nuts
- 8 3/8" USS Flat Washers Gr 5
- 8 3/8" Split Lock Washers Gr 5
- 4 3/8-16 Threaded U-Bolts
- 4 Square Plastic End Caps
- 8 3/8" Retaining Rings

### Tools Needed



Ratchet & Sockets  
5/8", 9/16" 18mm &  
19mm



Drill  
3/16" & 1/2"  
Multi-Depth or Step  
Drill Bit Recommended



Safety Glasses

Congratulations on your purchase of the Hyline Offroad Rock Sliders. All of our products are completely manufactured in our facility located in Perkasio, PA. They are designed and engineered by Offroad enthusiasts just like you to be rock solid. Hyline Offroad would like to thank you for your recent purchase and look forward to serving you in the future.

*Hyline Offroad Staff*

1. Remove any stock rock rails or factory tube steps from vehicle if equipped.

Note: You will also need to remove the factory Rubicon Rails if vehicle is equipped with them.

### **Passenger Side Installation:**

2. Remove the two existing bolts from underside of frame rail. This should drop the skid plate cross members just enough to slide the Passenger Side steel drill template in place. The Passenger Side Template will have a GREEN Dot located on it.
3. Insert the Passenger Side steel drill template between skid plates and the frame rail. Reinstall the two existing bolts and tighten. (Figure 1)

4. You can now drill the 4 holes in the side of the frame through the template using a 3/16" Drill Bit. Using a smaller drill bit will help with accuracy before drilling the final size 1/2" hole size.
5. After all 4 holes are pre-drilled you can remove the template. Then redrill all 4 holes open to 1/2". A Multi-Depth or Step Drill Bit is nicer for this operation because it's shorter and will cut through the metal quicker and easier.




**Figure 1, Template Shown is For 2 Door**

6. Before you install the Rock Slider onto your Jeep you may need to loosen more of the bolts on the gas tank skid plate and transmission skid plate in order to fit the Rock Slider Brackets in between the skid plate cross members and frame rail. You'll need at least a 1/4" gap or more to make fitting in the Rock Slider Brackets much easier.

7. Now install the supplied 3/8-16 Threaded U-Bolts by inserting one end first, then feeding and turning the U-Bolt until you fish it out the other hole. Do this before installing the Rock Sliders. Press on the provided Retaining Rings immediately after the U-Bolt is installed to prevent from slipping into frame. (Figure 2)

Helpful Tip When Installing the Retaining Rings: Once you have the U-Bolt in the frame, install a washer and nut on one side of the U-Bolt. This will hold U-Bolt in place and make placing the retainer ring on U-Bolt easier.


8. Now you're ready to install the Rock Slider (Much easier with two people). Slide the Rock Slider Brackets between the skid plate mounts and frame rail and install the two original bolts into the bottom. DO NOT TIGHTEN YET.
9. Fasten the 3/8-16 Hex Nuts onto U-Bolts with flat washers and lock washers. Do Not Overtighten These Nuts.
10. Tighten two bolts on the bottom of the frame.
11. The installation of the Passenger Side Rock Slider is now complete.



**Figure 2, Install U-Bolt by inserting one leg first as shown.**

### **Driver Side Installation:**

12. Remove the existing bolts from under frame rail, similar to passenger side.
13. Insert the Driver Side steel drill template (RED Dot) between skid plate cross member and the frame rail. Re-install the two bolts you previously removed to fasten template tight to frame.
14. Repeat and follow steps 4-10 for installation on the Driver Side.
15. Install Black Plastic Tube Caps in each end of Rock Slider tube.
16. You're installation is now complete.



**Figure 3 – U-Bolts Installed & Fastened**

**Send your Photos to [pics@HylineOffroad.com](mailto:pics@HylineOffroad.com) . If we choose any one of your pictures to be used on our website, We'll send you a FREE Hyline Offroad T-Shirt**

**\*\* IMPORTANT: PLEASE READ BEFORE INSTALLING**

**HYLINE OFFROAD, LLC WARRANTY**

HYLINE OFFROAD, LLC. LIMITED WARRANTY Hyline Offroad, LLC, warrants all products against manufacturer's defects in workmanship and material for a period of one (1) year from the date of sale. This warranty applies to manufacturer's defects only and does not cover damage or failure caused by natural causes or third parties.

If product failure does occur within the time period specified according to the provisions of this Warranty, then Hyline Offroad, LLC agrees to provide the replacement product free of charge, F.O.B. factory. This Warranty is valid only so long as the product is installed on the original vehicle. Removal of the product from this vehicle automatically invalidates this Warranty.

As described above, this warranty is expressly limited to the material cost of the product and does not extend to labor costs. Hyline Offroad, LLC will not be responsible for any costs incurred in the removal or reinstallation of the product furnished by manufacturer under this warranty.

CLAIMS PROCEDURE Submit Warranty claim in writing, by certified mail to Hyline Offroad, LLC, 1507 C West Park Avenue, Perkasio, PA 18944. The Claim Notice must state the date of this Notice, the nature of the defect, date of purchase and if already installed, the date of installation, if installed the name of installer and include Proof of Purchase.

This Warranty shall be for the benefit of the original owner only, and is non-transferable. This Warranty is valid in those states where permitted. Some states do not allow limitations on the length of an implied warranty, so the above limitation may not apply to you. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. You should check your local state laws to determine this. This Warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

THE WARRANTIES SET FORTH IN THE FOREGOING PROVISIONS ARE LIMITED TO THEIR PRECISE TERMS AND PROVIDE EXCLUSIVE REMEDIES EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES. THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, WHICH EXTEND BEYOND THE DESCRIPTION IN THE FOREGOING PROVISIONS. HYLINE OFFROAD, LLC EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY WITH REGARD TO THE PRODUCTS. HYLINE OFFROAD, LLC IS NOT LIABLE TO ANYONE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR BREACH OF ANY WARRANTY, EXPRESS OR IMPLIED. HYLINE OFFROAD, LLC IS NOT LIABLE FOR DAMAGES TO PERSON OR PROPERTY, CONSEQUENTIAL LOSSES, LOSS OF PROFIT, LOSSES OF PRODUCT IN STORE, OR THE LIKE, UNDER ANY CIRCUMSTANCES AND HYLINE OFFROAD, LLC'S LIABILITY IN ANY CIRCUMSTANCE IS SPECIFICALLY LIMITED BY THE TERMS OF THIS WARRANTY.

**HYLINE OFFROAD, LLC HOLD HARMLESS AGREEMENT**

1. In purchasing a Hyline Offroad, LLC Product™ I release, waive, discharge and covenant not to sue Hyline Offroad, LLC's officers, servants, agents, or employees (hereinafter referred to as Releasees) from any and all liability, claims, demands, actions and causes of action whatsoever arising out of or related to any loss, damage, or injury, including death, that may be sustained by me (or anyone else), any property belonging to me (or anyone else), whether caused by the negligence of the releasees or otherwise, while working on, using or any activity related to this product.
2. I am fully cognizant of any risks and/or hazards connected with the use of a this product and I elect to willingly engage in such use of this product knowing that the use may be hazardous to me and my property. I willingly assume full responsibility for any risks of loss, property damage or personal injury, including death, that may be sustained by me (or anyone else), or any loss or damage to property owned by me (or anyone else), as a result of using this product, whether caused by the negligence of releasees or otherwise.
3. I further agree to indemnify and hold harmless the releases from any loss, liability, damage or costs, including court cost and attorney fees, that they may incur due to my use of a this product, whether caused by negligence of releasees or otherwise.
4. It is my express intent that this Release and Hold Harmless Agreement shall bind the members of my family and spouse, if I am alive, and my heir's assigns and personal representative, if I am deceased, and shall be deemed as a release, waiver, discharge, and covenant not to sue the above named releasees. I further agree that this Waiver of Liability and Hold Harmless Agreement shall be construed in accordance with the laws of the State of Pennsylvania.

*By accepting and installing this product, I acknowledge and represent that I have read the above Warranty and Hold Harmless Agreement, understand it and accept it willingly as my own free act and deed; no oral presentations, statements, or inducements, apart from the foregoing written agreement, have been made; I am at least eighteen (18) years of age and fully competent; and I execute this Release for full, adequate and complete consideration fully intending to be bound by same.*

*If you do not agree with the preceding Hold Harmless Agreement, you may return the product and receive a full refund. Please, contact a Hyline Offroad sales representative and they will issue a call tag for the product in question. Once the product has been received by Hyline Offroad, inspected and accepted for return, a full refund will be issued.*